COATING SCHEDULE

STAINLESS GOLD STAIN

Substrate	Stainless Mirror / Hairline			
Product Item	Furniture or handicraft			
Positioning	Interior			
Finishing System	PU System			
Gloss Level	Sheen 90			

Finishing Condition Recommended				
Room humidity	Max 70 %			
Room temp.	28 - 32° C			



No	Application Step & Product Name	Mixing Ratio	Application Viscosity	CA [gr/m2]	Application Method	Drying Time Recommended
	Stainless Mirror/Hairline				Wipe with Thinner	
1	COLORING					
	USE-60 CLEAR GLOSS	400	10-11 sec	60-80	SPRAY	15 minutes
	HARDENER USE-60	100	NK-2			
	SS-700 STAINLESS GOLD	100				
	THINNER POLYURETHANE	100-200				
2	TOP COAT					
	USE-60 CLEAR GLOSS	400	10-11 sec	60-80	SPRAY	72 hours
	HARDENER USE-60	100	NK-2			
	THINNER POLYURETHANE	200				

Main Features:

Gold look

Perfect adhesion on stainless mirror

Available color: Gold, Rose Gold, Bronze and Transparant Black

Notes: Maximum thickness for every step of casting process is 2 cm

Surface Specificaition	Method	Result	Notes
Adhesion Test	ASTM D3359	Point 5B	Perfect